



► GFE-MCPE-C-IP67

Conventional Manual Call Point Outdoor Use-IP67

The **GFE-MCPE-C-IP67** is a Conventional Manual Call Point, designed and manufactured to comply with EN54-11, compatible with all GFE Conventional Control panels specially recommended for **outdoor use**.

The unit is supplied complete with a hinged flap which protects the trigger element from accidental activation and reduces malicious activations as 2 actions are required in order to activate the device.

A bi-colour LED flashes Green when the unit is connected to a control panel and is illuminated Red when in Alarm.

The GFE-MCPE-C-IP67 has been designed to deal with today's difficult and harsh environments. It is a unique fire alarm manual call point that mimics the feel of breaking glass whilst offering the user the benefits and safety advantages of a glass-free resettable operating element. Once activated a warning flag drops in to view easily identifying the call point that has been operated. A key can then reset the unit.

The GFE-MCPE-C-IP67 provides an ideal solution for most conventional fire alarm systems. Ideal for all outside applications such as oil rigs, ships, factories as well as wash down areas that are sensitive to broken glass.

TECHNICAL SPECIFICATIONS	GFE-MCPE-C-IP67
SUPPLY VOLTAGE	20-30 V DC
CURRENT - QUIESCENT	200 uA
CURRENT - DEVICE IN ALARM	50 mA - Alarm LED illuminated
MAX. CABLE SIZE	0.5-2.5 mm ²
COLOUR / CASE MATERIAL / PROTECTION	Red / ABS & Clear/ Polycarbonate - Flame Retardant 94 V0 / IP67
OPER. TEMPERATURE / MAX. HUMIDITY	-10°C to +50°C / 95% RH Non-Condensing
DIMENSIONS	111.9 (H) x 111.9 (W) x 81.3 (D) mm
ORDER CODE	DESCRIPTION
GFE-MCPE-C-IP67	IP67 Rated Conventional Call Point