



EN54-3 Type B
CERTIFIED
1328-CPR-0300



► VALKYRIE CS IP65

Conventional Wall Mount Sounder/ Beacon

The **VALKYRIE CS IP65** is a wall mounted Conventional Sounder/ Beacon with low power consumption. It is specifically designed to be used outdoors. **Four different tones** are available and selected using DIL switches 1 and 2.

Both continuous and pulsing outputs are provided via separate negative supply connections allowing for the presence of differentiated evacuation and alert sounds.

TECHNICAL SPECIFICATIONS	VALKYRIE CS IP65
SUPPLY VOLTAGE	20 V to 30 V DC
CURRENT - SOUNDER/ BEACON ACTIVE	10 mA - 280 mW @ 30 V DC
CURRENT - ALARM BEACON	1.4 mA
SOUNDER OUTPUT - CONTINUOUS	102 dB @ 1 m (Max.) - 97 dB @ 1 m (Min.)
SOUNDER OUTPUT - LOW FREQ.	103 dB @ 1 m (Max.) - 98 dB @ 1 m (Min.)
SOUNDER OUTPUT - HIGH FREQ.	110 dB @ 1 m (Max.) - 100 dB @ 1 m (Min.)
MAX. CABLE SIZE	2.5 mm ²
MAX. HUMIDITY	95% RH Non-Condensing
OPERATING TEMPERATURE	-20°C to 70°C
COLOUR / CASE MATERIAL	Red / ABS
PROTECTION CATEGORY	IP65 - Type B - Outdoor use
DIMENSIONS	112 (W) x 110 (H) mm inc. base
WEIGHT	315 g - 350 g including packaging
ORDER CODE	DESCRIPTION
VALKYRIE CS IP65	VALKYRIE CONVENTIONAL WALL SOUNDER - IP65 RATED
VALKYRIE CSB IP65	VALKYRIE CONVENTIONAL WALL SOUNDER/ BEACON - IP65 RATED