



EN54-3 Type A
CERTIFIED
1328-CPR-0289



► VULCAN 2 C

Conventional Sounder/ Beacon

Available in 2 colours

The VULCAN 2 C is a low consumption sounder designed to be used as an unobtrusive low profile sounder or as a base sounder to be installed in conjunction with a conventional detector. This leads to reduced installation costs and improves the aesthetics of the fire alarm system.

Four different tones are available and selected by jumpers. The Sound level can be adjusted if required, using the potentiometer.

The complete range is composed of 3 varieties in both base and wall mounted versions: Beacon, Sounder and combined Sounder/Beacon.

TECHNICAL SPECIFICATIONS	VULCAN 2 C
SUPPLY VOLTAGE	20 V to 30 V DC
CURRENT - QUIESCENT	1.1 mA
ALARM CURRENT - 800 TO 1000 HZ	4 mA sounder only - 5.5 mA inc. Beacon
ALARM CURRENT - 2.0 TO 3.0 KHZ	7 mA sounder only - 8 mA inc. Beacon
ALARM CURRENT - BEACON	2.5 mA
SOUNDER OUTPUT - LOW FREQ.	84 dB @ 1 m
SOUNDER OUTPUT - HIGH FREQ.	88 dB @ 1 m
MAX. CABLE SIZE	2.5 mm ²
MAX. HUMIDITY	95% RH Non-Condensing
OPERATING TEMPERATURE	-10°C to 55°C
COLOUR / CASE MATERIAL	White or Red / ABS - Transparent PC
DIMENSIONS	100 (D) x 50 (H) mm inc. base
WEIGHT	144 g inc. base
ORDER CODE	DESCRIPTION
VULCAN 2 CS	VULCAN 2 - CONVENTIONAL BASE SOUNDER
VULCAN 2 CSB	VULCAN 2 - CONVENTIONAL BASE SOUNDER WITH BEACON
VULCAN 2 CB	VULCAN 2 - CONVENTIONAL BEACON
VULCAN 2 L	OPAQUE LID FOR VULCAN 2
VULCAN 2 LT	TRANSPARENT LID VULCAN 2