

GFE-GAS-A

GFE-GAS-C-1224

GFE-GAS-C-220

GAS DETECTORS



GFE Gas detectors are designed and developed according to EN 50194 and EN 50291 European standards especially for home, office, hotel and industrial facilities for indoor use. GFE Gas Alarm detectors are designed to ensure the safety of the environments where LPG and natural gas has been used. It is a wall type and can be mounted on the wall with the mounting base. The GFE Gas Detectors gives audible and visual warning when the gas amount reaches the preset threshold level and provides immediate action for the people. GFE Gas Detectors has manufactured as Addressable and conventional with relay outputs which having 12/24V DC and 220V AC Voltage options.

TECHNICAL SPECIFICATIONS	
Power	12/24V DC and 220V AC 50Hz
Current	1.5 W (220V / 2.5 W)
Relay Out	250V AC / 7 Amps
Buzzer	85 dB (Internal)
Compatibility	EN 50194 – EN 50291
Life Time of Sensor	5 Years
Environment Temp.	Between -10 °C and 40°C
Humidity	95% RH
Dimensions & Weight	85x80x40 mm - 266 Gr.
DEVICE CODES	
GFE-GAS-A	Addressable Gas Detector – 24V DC
GFE-GAS-C-1224	Conventional Gas Detector – 12/24V DC w/RELAY
GFE-GAS-C-220	Conventional Gas Detector – 220V AC w/RELAY



İçerenköy Mah. Prof. Dr. Necmettin Erbakan Cad. No: 4/2 Ataşehir/İstanbul
Tel: +90 (216) 575 9696 Fax: +90 (216) 575 9097 bilgi@gfe.com.tr
<http://www.gfe.com.tr>

